

WO9939593

Publication Title:

AN APPARATUS IN AN INFUSOR FOR A LIQUID FOOD PRODUCT

Abstract:

Abstract of WO 9939593

(A1) The invention relates to an apparatus in an infusor (1). The infusor (1) is of the type which has an autoclave (2), with an inlet (3) in its upper region for the product which is to be heated, and an outlet (7) located in its lower region for the ready-treated product. The inlet (3) is provided with a distributor chamber (4) which divides the product into small droplets (20) when the product enters the autoclave (2). The infusor (1) further includes an inlet (8) for steam which is disposed in the lower region of the autoclave (2). The infusor (1) is also provided with at least one temperature gauge (15) placed in the upper region of the autoclave (2).; The temperature gauge (15) is disposed to control a valve (14) for the uncondensable gases which gather in the "cold" area (19) which is formed in the upper region of the autoclave, as a result of the placing of the steam inlet (8) in the lower region of the autoclave (2).

Courtesy of <http://v3.espacenet.com>




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: A23L 3/24, A23C 3/087	A1	(11) International Publication Number: WO 99/39593 (43) International Publication Date: 12 August 1999 (12.08.99)
(21) International Application Number: PCT/SE99/00161 (22) International Filing Date: 5 February 1999 (05.02.99) (30) Priority Data: 9800352-8 6 February 1998 (06.02.98) SE (71) Applicant (for all designated States except US): TETRA LAVAL HOLDINGS & FINANCE S.A. [CH/CH]; Avenue Général-Guisan 70, CH-1009 Pully (CH). (72) Inventor; and (75) Inventor/Applicant (for US only): PALM, Bengt [SE/SE]; Nylyckevägen 4, S-240 13 Genarp (SE). (74) Agent: BRUNNSTRÖM, Gunilla; AB Tetra Pak, Patent Dept., Ruben Rausing's gata, S-221 86 Lund (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: AN APPARATUS IN AN INFUSOR FOR A LIQUID FOOD PRODUCT**(57) Abstract**

The invention relates to an apparatus in an infusor (1). The infusor (1) is of the type which has an autoclave (2), with an inlet (3) in its upper region for the product which is to be heated, and an outlet (7) located in its lower region for the ready-treated product. The inlet (3) is provided with a distributor chamber (4) which divides the product into small droplets (20) when the product enters the autoclave (2). The infusor (1) further includes an inlet (8) for steam which is disposed in the lower region of the autoclave (2). The infusor (1) is also provided with at least one temperature gauge (15) placed in the upper region of the autoclave (2). The temperature gauge (15) is disposed to control a valve (14) for the uncondensable gases which gather in the "cold" area (19) which is formed in the upper region of the autoclave, as a result of the placing of the steam inlet (8) in the lower region of the autoclave (2).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

AN APPARATUS IN AN INFUSOR FOR A LIQUID FOOD PRODUCT

TECHNICAL FIELD

The present invention relates to an apparatus in an infusor for a liquid
5 food product, the apparatus being of the type which includes an autoclave
with an inlet for the product located in its upper region, the inlet being
arranged to divide the product entering the autoclave into small droplets,
the infusor further including an inlet for steam located in the lower region of
the autoclave and also an outlet located in the upper region for
10 uncondensable gases.

BACKGROUND ART

Heat-treating food products for increased shelf life is a well-known
and often-employed method. For example, the food product may be various
15 dairy produce such as milk, cream or yoghurt. The heat treatment may take
place in a plurality of ways, either directly or indirectly. Indirect methods
are, for instance, heating by means of different types of heat exchangers. Of
the direct methods, there are two major groups, injection or infusion with
steam. By employing a direct method, an extremely rapid heating will be
20 obtained which today is to be sought after since, in order to improve the
flavour properties of, for example, milk, it is often the intention to heat to
elevated temperatures for brief periods of time.

The present invention relates to an apparatus which employs infusion
heating. Infusion entails that a finely-divided liquid is heated in a steam
25 chamber. The principle of heating a liquid, for example a liquid food, by
injecting the food into a chamber filled with steam has been known since the
early part of the nineteenth century.

The first infusion heating plants were based on the same principle as
condensers with which surplus steam from various chemical processes was
30 condensed. The earlier plants thus displayed an infusor which consisted of
an autoclave with an inlet for product in the upper region of the autoclave.
The inlet discharged in a distributor chamber which divided the incoming
product into small, fine liquid droplets. In the bottom of the autoclave there
is an outlet for the heated product. The autoclave was further provided with
35 an inlet for steam which, in these early infusors, was located in the lower
region of the autoclave.

**CONFIRMATION
COPY**

The first infusors with their steam inlet placed in the lower region of the autoclave thereby automatically obtained a "colder" area in the upper regions of the autoclave. In this "colder" area of the infusor, the uncondensable gases which the product always contains gathers naturally.

5 The uncondensable gases may, for example, be oxygen, nitrogen and carbon dioxide, and these are emitted in connection with the product being heated. A minor quantity of the gases may also come from the steam employed in the process. By obtaining a natural gathering of the gases with a very slight admixture of steam, it is thus easy to lead them off by means of an outlet

10 placed in the upper region of the autoclave.

But since these early infusors suffered from another drawback, this concept was abandoned. The drawback was that when such infusors were used, for example for milk, the steam which, at a low level in the autoclave, is injected in towards the finely-divided liquid droplets caused the droplets

15 to change direction and many of the droplets became stuck to the hot inner walls in the infusor, where burning of the product to such walls was the immediate outcome. The burning of product onto the walls entails major hygienic problems and such burnt product is extremely difficult to wash off.

In order to obviate the problem of burning of the product on the inner walls of the infusor, the steam inlet was placed in the upper region of the infusor. The steam was supplied from above, over the distributor chamber of the product, so that the droplets are not disrupted in the fall down through the steam chamber. But the admission of steam concurrently with the admission of product also suffers from its drawbacks. This type of steam

20 admission may give rise to burning of the product around or in the distributor apertures or distributor gaps displayed by the distributor chamber. This disrupts the heating of the product, the temperature of the product falls, whereupon the steam pressure must be increased and higher temperature differences will occur between product and steam. By designing

25 the distributor apertures such that they have a very thin edge out towards the steam chamber, it is possible to solve the problem in that there will be very thin burnt product layers which are easily broken off before they become disruptive.

But the concurrent admission of steam also resulted in it not being

35 possible to create the "cold" area in the upper region of the autoclave. The uncondensable gases have no natural point of collection. The uncondensable

gases may also readily remain trapped in pockets in the downwardly flowing steam and there very readily occurs admixture of steam into the uncondensable gases. This gives a considerably poorer degree of heating of the product, which must be compensated for by an unnecessarily high steam pressure and greater temperature difference between steam and product. The consumption of steam in the process will also be considerably higher, since it is difficult to separate the steam and the uncondensable gases on discharge of the gases.

10 OBJECTS OF THE INVENTION

One object of the present invention is, by combining a steam inlet which is placed low with a temperature gauge which controls the discharge of the uncondensable gases, to obtain a natural separation of gases and steam and an automatic discharge of these gases.

15 A further object of the present invention is to reduce steam consumption in the process, since steam and uncondensable gases are not intermixed as easily.

SOLUTION

20 These and other objects have been attained according to the present invention in that the apparatus of the type described by way of introduction has been given the characterizing features that the infusor has at least one temperature gauge placed in the upper region of the autoclave, the pressure gauge being, via a temperature regulator, disposed to control an outlet valve for the uncondensable gases.

25 Preferred embodiments of the present invention have further been given the characterizing features as set forth in the appended subclaims.

30 BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWINGS

One preferred embodiment of the present invention will now be described in greater detail hereinbelow, with reference to the accompanying Drawings, in which:

35 Fig. 1 is a side elevation, partly in section, of an infusor according to the present invention; and

Fig. 2 is a flow diagram of a plant for heat treatment by means of infusion heat.

The Drawings show only those parts and details essential to an understanding of the present invention.

5

DESCRIPTION OF PREFERRED EMBODIMENT

Fig. 1 shows, in side elevation, an infusor 1 according to the present invention. The infusor 1 consists substantially of a conventional autoclave 2. In its upper region, the autoclave 2 has an inlet 3 for the product which is to be heat treated in the infusor 1. The product inlet 3 terminates with a distributor chamber 4. The distributor chamber 4 is centrally placed in the autoclave and has, on its lower wall 5, a large number of apertures or gaps. The apertures or gaps are intended to finely divide the incoming product so that the product, when it enters the autoclave 2, forms a large number of small, fine droplets 20 which fall down through the autoclave 2.

In the lower, preferably lowermost, region of the autoclave 2, where the autoclave 2 forms a conical termination 6, there is disposed an outlet 7 for the product which has been heat treated in the infusor 1. The lower region of the conical termination 6 of the autoclave 2 functions as a retainer cell where the product stays for a certain period of time before being pumped further for additional treatment.

Furthermore, the infusor 1 is, in the lower region of the autoclave 2, provided with an inlet 8 for steam 21. The steam inlet 8 is placed far down in the autoclave 2, preferably above the conical termination 6 of the autoclave 2 and a distance from the liquid surface 9 which is formed by the heat treated product, when the product stays in the autoclave 2 at a certain temperature and before it leaves the autoclave 2. The steam inlet 8 is, via an insulated distributor chamber 10, connected to a concentric aperture 11 provided in the casing surface 12 of the autoclave 2.

In the upper region of the autoclave 2, there is disposed an outlet 13 for uncondensable gases. The outlet 13 is provided with a controllable valve 14. In the upper region of the autoclave 2, there is also placed at least one temperature gauge 15, which, via a temperature regulator 16, controls the outlet valve 14. In the preferred embodiment, the autoclave 2 is provided with an additional two temperature gauges 17, 18, preferably placed such

that one gauge 17 is located on a higher level than the gauge 15, and the other gauge 18 is on a lower level than the gauge 15.

The incoming product entering the infusor 1 is pumped through a conduit to the inlet 3 to the upper region of the autoclave 2. The incoming
5 product (which may, for example, consist of milk) is normally at a temperature of 75-82°C, but in certain applications up to 120°C. From the inlet 3 and the distributor chamber 4, the product passes through a large number of apertures or gaps provided in the lower wall 5 of the distributor
10 chamber 4. The product thereby forms a large number of small droplets 20 which fall freely down through the autoclave 2 until they reach the liquid surface 9. On their way down through the autoclave 2, the product droplets 20 meet pressurized steam 21 which is at a temperature of approx. 120-170°C, preferably 140-150°C.

By condensation of the steam, the steam 21 rapidly heats the product
15 droplets 20 to the desired temperature and when the droplets 20 reach the liquid surface 9, the product has attained the desired temperature. The distance between the distributor chamber 4 for product and the liquid surface 9 should be so great that the product droplets 20 have time to be heated to the desired temperature. The ready-heated product will, for a
20 certain period of time, stay in the conical termination 6 of the autoclave 2 before leaving the infusor 1 through the outlet 7.

As a result of the admission of steam 21 concentrically in the autoclave 2, there will be obtained a very uniform distribution of the steam 21 within the autoclave 2 and there is very little risk that the inflowing steam
25 21 disrupts the product droplets 20. In that the product droplets 20 may fall relatively straight down without disruption, product spattering on the hot inner walls of the autoclave 2 is reduced to a minimum, and thereby the burning of product on the walls of the autoclave is also reduced.

During the heating process, uncondensable gases 22, such as oxygen,
30 nitrogen and carbon dioxide, are released from the product. A certain quantity of uncondensable gases 22 also comes from the steam 21 which is employed in the process. In that the infusor 1 has a steam inlet 8 placed in the lower region of the autoclave 2, there will naturally be obtained a "cold" area 19 in the upper regions of the autoclave 2. The uncondensable gases 22
35 quite naturally gather in this "cold" area 19, with a very slight admixture of steam 21 from the process. The "cold" area prevents the apertures or gaps in

the lower wall 5 of the distributor chamber 4 from being heated by steam at elevated temperature and the burning of product in the apertures or gaps - or on the lower wall 5 - of the distributor chamber 4 is thereby avoided.

5 The temperature regulator 16 is given a norm value which exceeds the temperature of the incoming product by a few degrees. When the temperature gauge 15 reads off this norm value, a signal passes to the controllable outlet valve 14. The valve 14 opens and the uncondensable gases 22 are evacuated. In order to obtain a suitably large "cold" area 19, the preferred embodiment calls for the employment of a further two
10 temperature gauges 17, 18, which in principle function as maximum and minimum temperature guards, respectively. The "cold" area 19 should not be allowed to extend downwards in the autoclave 2, since this may have a harmful effect on the heating of the product. Nor should the "cold" area shrink to such a slight volume that the natural gathering of the
15 uncondensable gases 22 is not realised. Alternatively, only gauges 15, 17 may be employed, where the first gauge 15 regulates the valve 14 and the second gauge 17 functions either as a maximum temperature guard or as a minimum temperature guard, depending on where it is placed in relation to the first gauge 15.

20 Fig. 2 shows how an infusor 1 is included as a part in a plant for the heat treatment of a liquid food product by means of infusion heat. The incoming product 30 passes via a balance tank 31 and a pump 32. In a heat exchanger 33, for example a plate heat exchanger, the product is pre-heated to the desired temperature, normally of the order of 75-82°C, but
25 temperatures of up to 120°C may occur. The thus heated product is led in a conduit to the infusor 1 and is heat treated there using the above-described method.

The ready-treated product is led from the infusor 1 to an expansion vessel 34 where the excess of water which the product has obtained as a
30 result of the infusion heating is once again removed. Via a pump 35 and possibly a homogenizer 36, the product is led further to a cooler 37, for example a plate heat exchanger, where it is cooled to the desired temperature. The product then leaves the plant through a conduit 38 for further treatment or to final filling and packing in consumer packages.

35 As will have been apparent from the foregoing description, the present invention realises an apparatus in an infusor 1 which assists in

making it possible to admit steam 21 at a low level in the autoclave 2, without the steam flow 21 disrupting the fall of the product droplets 20 through the autoclave 2. Given that the steam inlet is placed in the lower region of the autoclave 2, there will also be created a "cold" area 19 in the
5 upper region of the autoclave 2, which assists in making it possible to evacuate the uncondensable gases 22 formed in the process, both simply and without unnecessary quantities of accompanying steam 21.

The present invention should not be considered as restricted to that described above and shown on the Drawings, many modifications being
10 conceivable without departing from the scope of the appended Claims.

WHAT IS CLAIMED IS:

1. An apparatus in an infusor (1) for a liquid food product, the apparatus being of the type which includes an autoclave (2) with an inlet (3) for the product located in its upper region, said inlet (3) being arranged to divide the product entering the autoclave (2) into small droplets (20), the infusor (1) further including an inlet (8) for steam located in the lower region of the autoclave (2) and also an outlet (13) located in the upper region for uncondensable gases (22), characterized in that the infusor (1) has at least one temperature gauge (15) placed in the upper region of the autoclave (2), said temperature gauge (15) being disposed, via a temperature regulator (16), to control an outlet valve (14) for the uncondensable gases (22).

2. The apparatus as claimed in Claim 1, characterized in that the placing of the steam inlet (8) in the lower region of the autoclave (2) creates a "cold" area (19) in the upper region of the autoclave (2).

3. The apparatus as claimed in any of the preceding Claims, characterized in that the temperature regulator (16) is given a norm value which exceeds the temperature of the incoming product in the autoclave (2) by a few degrees.

4. The apparatus as claimed in any of the preceding Claims, characterized in that the autoclave (2) has, in its upper region, three temperature gauges (15, 17, 18), where one of the temperature gauges (17) is placed above the temperature gauge (15) and another of the temperature gauges (18) is placed beneath the temperature gauge (15); and that they are disposed such that the upper gauge (17) functions as a maximum temperature guard and that the lower gauge (18) functions as a minimum temperature guard.

1/2





Fig 1

**Fig 2**

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/00161

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A23L 3/24, A23C 3/087

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A23C, A23L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4787304 A (BRONNERT), 29 November 1988 (29.11.88), column 5, line 46, claims 1-3 --	1-4
A	AU 610233 B (APV PASILAC A/S), 2 March 1989 (02.03.89), figure 2, abstract --	1-4
A	US 4851250 A (BRONNERT), 25 July 1989 (25.07.89), abstract -----	1-4

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

19 May 1999

Date of mailing of the international search report

31 -05- 1999

Name and mailing address of the ISA:

Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Inger Löfgren
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/05/99

International application No.

PCT/SE 99/00161

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	4787304	A	29/11/88	NONE	
AU	610233	B	02/03/89	NONE	
US	4851250	A	25/07/89	US 4776268 A	11/10/88